

etolit Clean

Special cleaner for automatic cleaning systems

Application / Dosage

- > **etolit Clean** is suitable for professional only
Application automatically or manually.

**Dosage: Manual: leave undiluted for 15 - 30 min,
steam for 5 - 10 min with max 50°C and rinse with
clear water**

- > Dosing is carried out manually via the Multi-Sol-Set or according to the operating instructions of the device manufacturer
- > Place **etolit Clean** only in the storage container provided for this purpose
- > Observe the application notes in the device manual

Product Features

- > Automatically removes encrusted and burnt-in oil and grease stains
- > Cleanses powerfully and intensively

Application

- > For combi steamers with automatic cleaning system or for manual cleaning
- > Not suitable for aluminium and painted surfaces

Important Information

- > **etolit Clean** is suitable for all food processing companies
- > Do not mix with other products, do not transfer product into other containers
- > Rinse with clean water after cleaning
- > Higher temperatures should be avoided, especially with stainless steel surfaces, as this can lead to discoloration and corrosion

etolit Clean

Special cleaner for automatic cleaning systems

Technical Data

- > Colour..... Red liquid
- > Density..... 1,1 g/ml
- > pH-value 14
- > Storability..... 4 years
- > Storage conditions.... Between 5 and 30°C

Ingredients

Ingredients according to the detergents regulation:
Less than 5 % amphoteric surfactants

- > Chlorine: no
- > Phosphate: no
- > NTA: no

Residual Emptying/ Disposal

- > Empty containers are recyclable and can be disposed of by the end user via DSD.
- > Information on the disposal of product residues can be found in the respective safety data sheet.

Sales Units



Can 10 l
Art.-No.: 2000339

Hazard information/ Environmental factors



Further information on our products and the EC safety data sheets can be found on :
www.etol.de

