

etolit Smoke Resin Remover

Cleaner, highly alkaline, for all smoking and cooking systems

Application / Dosage

> **etolit Smoke Resin Remover** is suitable for professional only

Dosage: 150 - 350 ml / 10 l water at 60°C with 10 - 20 minutes exposure time

- > The dosage is carried out via a spray gun or a multi-sol set
- > In the case of automatic cleaning, the instructions of the manufacturer of the smoking or cooking equipment must be observed

Product Features

- > Powerfully cleans all smoking and cooking equipment
- > Has a high cleaning power, even for stubborn dirt
- > Only use on alkali-resistant surfaces

Application

- > Dissolves oils, fats, resins and organic deposits intensively
- > Not suitable for aluminium and painted surfaces

Important Information

- > **etolit Smoke Resin Remover** is suitable for all food processing companies
- > Do not mix with other products, do not transfer product into other containers

etolit Smoke Resin Remover

Cleaner, highly alkaline, for all smoking and cooking systems

Technical Data

- > Colour..... Brown liquid
- > Density..... 1,4 g/ml
- > pH-value 14
- > Storability..... 4 years
- > Storage conditions.... Between 5 and 30°C

Ingredients

Ingredients according to the detergents regulation:
5 - 15 % non-ionic surfactants

- > Chlorine: no
- > Phosphate: no
- > NTA: no

Residual Emptying/ Disposal

- > Empty containers are recyclable and can be disposed of by the end user via DSD.
- > Information on the disposal of product residues can be found in the respective safety data sheet.

Sales Units



Can 12 kg
Art.-No.: 2000305

Hazard information/ Environmental factors



Further information on our products and the EC safety data sheets can be found on :
www.etol.de

